



Tipe Rantai	ISO BS/DIN No.	Pitch P	Dia. Roller R	Inner Width b1	Jarak Antara Inner Plate W	Pin				link Plate		Average Breaking Loads kgf.
						D	L1	L2	L	T	H	
SINGLE STRAND												
F - 00406 S	RS25-1	6.35	3.30	3.30	3.18	2.31	3.80	4.50	-	0.74	5.84	418
F - 00909 S	RS35-1	9.53	5.08	5.08	4.78	3.59	5.85	6.85	13.50	1.25	9.00	999
F - 00812 S	RS37-1	12.70	7.80	7.80	3.40	3.63	5.10	5.90	12.45	1.00	9.80	826
F - 00812 S	RS38-1	12.70	7.80	7.80	4.80	3.63	6.00	7.10	14.10	1.10	9.80	826
F - 01012 S	RS41-1	12.70	7.77	7.77	6.38	3.59	6.75	7.95	15.10	1.25	9.80	1,050
F - 02012 S	RS40-1	12.70	7.92	7.92	7.95	3.97	8.25	9.95	17.90	1.50	12.00	1,805
F - 02015 S	RS50-1	15.88	10.16	10.16	9.53	5.09	10.30	11.90	22.50	2.00	15.00	2,896
F - 04019 S	RS60-1	19.05	11.91	11.91	12.70	5.96	12.85	14.75	28.20	2.40	18.10	4,099
F - 07025 S	RS80-1	25.40	15.88	15.88	15.88	7.94	16.25	19.25	36.60	3.20	24.10	7,301
F - 10031 S	RS100-1	31.75	19.05	19.05	19.05	9.54	19.75	22.85	43.70	4.00	30.10	10,911
F - 15038 S	RS120-1	38.10	22.23	22.23	25.40	11.11	24.90	28.90	55.00	4.80	36.20	15,092
F - 19044 S	RS140-1	44.45	25.40	25.40	25.40	12.71	26.90	31.70	59.50	5.60	42.20	19,681
F - 26050 S	RS160-1	50.80	28.58	28.58	31.75	14.29	31.85	36.85	70.20	6.40	48.20	26,003
F - 34057 S	RS180-1	57.15	35.71	35.71	35.72	17.46	35.65	42.45	80.60	7.15	54.20	34,262
F - 43063 S	RS200-1	63.50	39.68	39.68	38.10	19.85	39.00	44.80	87.30	8.00	60.30	43,542
F - 63076 S	RS240-1	76.20	47.63	47.63	47.63	23.81	47.90	55.50	106.70	9.50	72.40	63,528
DOUBLE STRAND												
F - 00806 S-2	RS25-2	6.35	3.30	3.30	3.18	2.31	6.95	7.75	-	0.74	5.84	836
F - 00209 S-2	RS35-2	9.53	5.08	5.08	4.78	3.59	10.90	11.90	24.50	1.25	9.00	1,999
F - 00312 S-2	RS40-2	12.70	7.92	7.92	7.95	3.97	15.45	17.15	33.50	1.50	12.00	3,600
F - 00612 S-2	RS50-2	15.88	10.16	10.16	9.53	5.09	19.35	21.15	41.80	2.00	15.00	5,802
F - 00819 S-2	RS60-2	19.05	11.91	11.91	12.70	5.96	24.25	26.25	52.60	2.40	18.10	8,199
F - 14025 S-2	RS80-2	25.40	15.88	15.88	15.88	7.94	30.90	33.90	67.50	3.20	24.10	14,582
F - 21031 S-2	RS100-2	31.75	19.05	19.05	19.05	9.54	37.70	40.80	81.50	4.00	30.10	21,822
F - 38030 S-2	RS120-2	38.10	22.23	22.23	25.40	11.11	47.60	51.60	103.20	4.80	36.20	30,184
F - 39044 S-2	RS140-2	44.45	25.40	25.40	25.40	12.71	51.35	56.15	112.30	5.60	42.20	39,361
F - 52050 S-2	RS160-2	50.80	28.58	28.58	31.75	14.29	61.15	66.15	132.20	6.40	48.20	52,006
F - 68057 S-2	RS180-2	57.15	35.71	35.71	35.72	17.46	68.75	75.35	151.10	7.15	54.20	68,627
F - 86063 S-2	RS200-2	63.50	39.68	39.68	38.10	19.85	74.85	80.65	161.20	8.00	60.30	86,982
F - 127076 S-2	RS240-2	76.20	47.63	47.63	47.63	23.81	91.90	99.40	198.40	9.50	72.40	127,465
TRIPPLE STRAND												
F - 00106 S-3	RS25-3	6.35	3.30	3.30	3.18	2.31	10.15	10.95	-	0.74	5.84	1,264
F - 00309 S-3	RS35-3	9.53	5.08	5.08	4.78	3.59	16.00	16.90	34.60	1.25	9.00	2,998
F - 00512 S-3	RS40-3	12.70	7.92	7.92	7.95	3.97	22.65	24.15	47.90	1.50	12.00	5,404
F - 00816 S-3	RS50-3	15.88	10.16	10.16	9.53	5.09	28.40	30.20	59.90	2.00	15.00	8,698
F - 01219 S-3	RS60-3	19.05	11.91	11.91	12.70	5.96	35.65	38.15	75.50	2.40	18.10	12,339
F - 02225 S-3	RS80-3	25.40	15.88	15.88	15.88	7.94	45.60	48.50	96.90	3.20	24.10	21,924
F - 32031 S-3	RS100-3	31.75	19.05	19.05	19.05	9.54	55.65	58.75	117.30	4.00	30.10	32,733
F - 45038 S-3	RS120-3	38.10	22.23	22.23	25.40	11.11	70.40	74.40	148.60	4.80	36.20	45,275
F - 59044 S-3	RS140-3	44.45	25.40	25.40	25.40	12.71	75.85	80.75	161.30	5.60	42.20	59,144
F - 78050 S-3	RS160-3	50.80	28.58	28.58	31.75	14.29	90.45	95.45	190.70	6.40	48.20	78,008
F - 102057 S-3	RS180-3	57.15	35.71	35.71	35.72	17.46	101.70	108.50	216.90	7.15	54.20	102,991
F - 130063 S-3	RS200-3	63.50	39.68	39.68	38.10	19.85	110.75	116.45	233.00	8.00	60.30	130,524

